Motor M63/I
with planetary gear P62

excellent drives

- Steel gearhousing, aluminium gearflange
- Other reductions, output shaft or connection cable on request



Gear reduction table M63xXX/I+ P62

Application on request

Gear reduction	Number of gear stages	Efficiency of the gear	Speed at motor-speed 3000rpm	Continuous torque			
				M63x25/I L1 = 99 mm	M63x40/I L1 = 114 mm	M63x60/I L1= 134 mm	
[i = x:1]	[x]	[%]	[1/min]	[Ncm]	[Ncm]	[Ncm] 12V	[Ncm] 24V
3,7	1	80	810	41,4	53,3	65,1	88,8
7	1	80	428	78,4	101	123	168
14	2	75	214	147	189	231	315
25	2	75	120	262	338	413	563
46	2	75	65	483	621	759	1035
93	3	70	32	911	1172	1535	2093
169	3	70	18	1656	2129	2789	3803
308	3	70	9,7	3018	3881	5000*	5000*

*) Motor have to be operated with current limitation

General gear data

Number of gear stages	[x]	1	2	3
Maximum torque	[Ncm]	800	2500	5000
Permissible shaft load	[N] (axial / radial)	70 / 240	100 / 360	150 / 520
Gear length L2	[mm]	45,7	62,5	79,4

Stand: 4. August 2020 – changes reserved

Kählig Antriebstechnik GmbH
Pappelweg 4
D-30179 Hannover/Germany

fon: +49 511 67493-0
fax: +49 511 67493-67
info@kag-hannover.de

www.kag-hannover.de